09/986,446   Attorney Docket No.: 20496/365

a second filter, said second filter disposed downstream from said feed in

said flow direction,

wherein said second filter comprises a porous filter medium in the form of

a deep-bed filter,

wherein said first filter is configured to operate based on cake filtration.

Claim 13. (Cancelled).

Claim 14. (Previously Presented). A device according to claim 12 wherein said

first filter comprises a ceramic foam plate.

Claim 15. (Previously Presented). A device according to claim 14 wherein said

ceramic foam plate has a thickness of 5 to 33 mm.

Claim 16. (Previously Presented). A device according to claim 14 wherein said

ceramic foam plate has a thickness of 10 to 15 mm.

Claim 17. (Previously Presented). A device according to claim 12 wherein said

first filter comprises a sintered material.

Claim 18. (Previously Presented). A device according to claim 12 wherein said

first filter comprises a material deposited by CVD.

Claim 19. (Cancelled).

Claim 20. (Cancelled).

Claim 21. (Previously Presented). A device according to claim 20 wherein said

deep-bed filter is a loose-fill bed filter.

2

09/986,446   Attorney Docket No.: 20496/365

Claim 22. (Previously Presented). A device according to one of claims 12 to 21 wherein a filter selected from the group consisting of said first filter and said second filter are configured to be heated.

Claim 23. (Previously Presented) A device according to one of claims 12 to 21 wherein both said first and second filters are configured to be heated.

Claim 24. (Currently Amended). A method for filtering and adding a grain refining material to a metal melt, said method comprising:

filtering said melt using a porous medium <u>as a first filter</u>;

adding said grain-refining material to said melt after said filtering said melt using a porous medium; and

filtering said melt using a second filter after said adding,

wherein said second filter comprises a porous filter medium in the form of a deep-bed filter,

<u>wherein said first filter is configured to operate based on cake filtration.</u>

3